

SANSTICK 160S

\$615.00

Comes with 6.5ft. Work and Electrode lead, 120/240 vac adaptor and Carry case.

Need to know:

- STICK (SMAW) (**E6010 Performance**)
 - TIG (GTAW) Lift Start
 - **PFC—Power Factor Correction.** Will use less current when operating on 120 VAC.
 - Preset Hot Start & Arc Force
 - CSA Certification
 - 3 Year Warranty
-
- **Input Voltage** 115/230 VAC 1 Phase
 - Input Frequency 50/60 Hz
 - Output range 8 – 125 Amps (115V), 10 - 160 Amps (230V)
 - Rated Output 125A @ 30% Duty Cycle (115v 1 phase), 160A @ 40% Duty Cycle (230v1 phase)
 - Max OCV 65
 - Consumable Size 3/32" - 5/32" STICK electrode
 - Dimensions (HxWxD) 9" x 5.5" x 14.4" (230 x 140 x 365mm)
 - Weight 17.6 lbs. (8 kg)



SANARG 180AP

\$1,580.00

Comes with: 10ft. Work and Electrode lead, 120/240 vac adaptor, 10ft. TIG Torch w/Remote On/OFF & Current control, Regulator/Flowgauge w/13ft. Gas Hose.

Need to know:

- AC/DC TIG (GTAW) Lift & HF Start with Rapid Pulse control.
 - STICK (SMAW)
 - Auto Switch - Multi-voltage 115/208-230 VAC, single phase
 - PFC—Power Factor Correction. Will use less current when operating on 120 VAC.
 - True square wave output with AC Frequency & Balance control
 - CSA Certification
 - 3 Year Warranty
-
- Input Voltage 115/230 VAC 1 Phase
 - Input Frequency 50/60 Hz
 - Output range 5 – 140 Amps (115V), 5 - 200 Amps (230V)
 - Rated Output 140A @ 40% Duty Cycle (115v 1 phase), 180A @ 40% Duty Cycle (230v1 phase)
 - Max OCV 65



SANMIG 200MF

\$1,552.00

Comes with: 10ft. Work and Electrode lead, 120/240 vac adaptor, 10ft. Mig Gun, Regulator/Flow gauge w/13ft. Gas Hose.

Need to know:

- Full Multi-Process DC MIG/ L-TIG / STICK
 - Built-in Wire feeder
 - Synergic – Simple Setup
 - Auto Switch - Multi-voltage 115/208-230 VAC, single phase
 - PFC—Power Factor Correction. Will use less current when operating on 120 VAC.
 - Adjustable Inductance & Hot Start
 - Digital Amperage and Voltage Meter
 - Remote receptacle for Spool Gun
 - CSA Certification
 - 3 Year Warranty
-
- Input Voltage: 115/230 VAC 1 Phase
 - Input Frequency: 50/60 Hz
 - Output range: 5 – 140 amps (115V), 5 – 200 amps (230V)
 - 10 – 26 volts (115/230V)
 - 0.030 - 0.035 dia. (.8 - .9 mm) Wire
 - 7 - 425 IPM Wire Feed Speed
 - Material Thickness: 1/4"
 - Dimensions: (HxWxD) 10.2"x5.1"x12.6" (260x130x320mm)
 - Weight: 39.2 lbs. (17.8 kg)



SANMIG 250MF

\$2,052.00

Comes with: 10ft. Work and Electrode lead, 120/240 vac adaptor, 10ft. Mig Gun w/remote control, Regulator/Flow gauge w/13ft. Gas Hose.

Need to know:

- Full Multi-Process DC MIG/ L-TIG / STICK
 - Built-in Wire feeder
 - Synergic – Simple Setup
 - Auto Switch - Multi-voltage 115/208-230 VAC, single phase
 - PFC—Power Factor Correction. Will use less current when operating on 120 VAC.
 - Adjustable Inductance & Hot Start
 - Digital Amperage and Voltage Meter
 - Remote receptacle for Spool Gun
 - CSA Certification
 - 3 Year Warranty
-
- Input Voltage: 115/230 VAC 1 Phase
 - Input Frequency: 50/60 Hz
 - Output range: 5 – 140 amps (115V), 5 – 250 amps (230V)
 - 10 – 26 volts (115/230V)
 - 0.030, 0.035, 0.045" dia. (.8, .9, 1.2 mm) Wire
 - 7 - 425 IPM Wire Feed Speed
 - Material Thickness: 3/8"
 - Dimensions: (HxWxD) 10.2"x5.1"x12.6" (260x130x320mm)
 - Weight: 48.5 lbs. (22 kg)



SanRex


The Metalworker's Choice.

SANCUT 638

\$1,450.00

Need to know:

- Cut Capacity:
 - Recommended 1/4" (6.3mm)
 - 120 vac, 3/8" (9.5mm) 240 vac.
 - Maximum 1/2" (12.7 mm) 120 vac, 3/4" (19mm) 240 vac.
 - Pierce 1/4" (6.3mm) 120 vac, 3/8" (9.5mm) 240 vac.
- 120/240 vac Dingle Phase
- 20ft. Torch
- Auto Air Regulator
- CSA Certified
- 3 Year Warranty



SANARG 200AP

\$3,500.00

Need to know:

- AC/DC TIG (GTAW) Lift & HF Start with Rapid Pulse control.
 - STICK (SMAW)
 - Smart Switch - Multi-voltage 208-230/460 VAC, single/Three phase
 - True square wave output with AC Frequency & Balance control
 - Program Save/Load Function
 - Pre and Post Flow gas timer.
 - Adjustable Hot Start
 - Digital Amperage and Voltage Meter
 - 14 pin Remote amperage and contactor receptacle
 - Simple Automation I/O.
 - 3 Year Warranty
-
- Input Voltage: 208-230/460 VAC 1/3 Phase
 - Input Frequency: 50/60 Hz
 - Output range: 5 - 320 Amps DC / 10- 300 Amps AC
 - Rated Output: 200A @ 20% Duty Cycle (STICK/TIG)
 - Max OCV: 65
 - Dimensions: (HxWxD) 14.2" x 7.1" x 16.5" (360 x 180 x 420 mm)
 - Weight: 53 lbs. (24 kg)



SANFEED FIELD 4HD

\$2,320.00

Need to know:

- Voltage Sensing
 - TWECO® Gun Connection
 - Heavy Duty Plastic Case
 - Digital Meters (Voltage and Amperage)
 - Heavy Duty 4 driven Roll System
 - Inch/Purge
 - Gun Trigger Hold (2T/4T)
 - Electronic Speed Control & Dynamic Breaking.
 - Heavy Duty Contactor
 - 3 Year Warranty
-
- Input Voltage: 15 - 100 VDC
 - Output range: 58 - 850 IPM (1.5 - 22 m/min)
 - 0.024" - 5/64" (0.6 - 2.0mm) Solid or Flux Cored.
 - Rated Output: 400A @ 100% Duty Cycle
 - Dimensions: (HxWxD) 13.38"x12.60"x21.65" (340x320x550mm)
 - Weight: 35.27 lbs. (16 kg)



SANMIG 400M

\$4,400.00

Need to know:

- Full Multi-Process MIG/ L-TIG / STICK/CAG (E6010 Compatible)
 - Standards compliant integrated voltage reduction device (VRD)
 - 14 Pin Receptacle
 - Simple Automation I/O.
 - Smart Switch - Multi-voltage 208-230/460 VAC, single/three phase
 - Adjustable Inductance
 - Adjustable Arc Control
 - Adjustable Hot Start
 - Digital Amperage and Voltage Meter
 - Job Save/Load
 - 3 Year Warranty
-
- Input Voltage: 208-230/460 VAC 1/3 Phase
 - Input Frequency: 50/60 Hz
 - Output range: 5 - 400 Amps. 10 - 36 volts (115/230V)
 - Rated Output: 300A @ 60% Duty Cycle, 400A @ 25% Duty Cycle
 - Max OCV: 65
 - Dimensions: (HxWxD) 16.5"x8.3"x17.7" (420x210x450mm)
 - Weight: 55.6 lbs. (25.22 kg)



400M with HD MIG Kit shown.
\$8,800.00

R and H Gas

Ph: 614-595-8389

www.randhgas.com

320 S. State St. Westerville, OH. 43081